

Kubota



KUBOTA ZERO-TURN MOWER

Z

ZD331 Rear Discharge Mower

The Z331 provides the dexterity and performance demanded by rear discharge applications.

Kubota's ZD331 with rear discharge mower offers greater trim ability while reducing the likelihood of thrown objects.

- 31HP Kubota diesel engine
- 60"-wide mower deck
- Adjustable front axle (oscillating/rigid)
- Semi-pneumatic (flat-free) front caster tyres
- High-performance HST transmission
- Full-flat operator platform
- High-back deluxe suspension seat
- Adjustable speed control levers
- Hands-free hydraulic deck lift
- Hands-free parking brake
- Rear Fender Extensions
- Maintenance lift



60"
Pro Commercial
Mower

60" Rear Discharge Mower

Our steel rod reinforced, 60" rear-discharge mower provides the ZD331 with exceptional performance. This professional 5.5" deep deck gives you a fast and clean cut even in tall grass or weeds. Reducing the likelihood of thrown objects is a certain benefit, especially near streets, schools, and parks because grass is discharged behind the mower rather than to the side. Moreover, it offers the operator greater control in confined spaces such as in cemeteries or around flowerbeds.

Steel Rod Reinforced Deck

The rear discharge deck is reinforced with 1" diameter steel rods on the skirt to improve the durability and longevity. Additionally, the reinforcements are easily replaceable if damaged or worn.



*This information is sourced from overseas and may not necessarily apply locally. It is essential that you confirm specifications and other information with your local Kubota dealer.



Specifications

Model		ZD331	
		ZD331RP-60R	
Engine	Model	Kubota D1305-E3-ZD	
	Type	Diesel, liquid-cooled (3 cyl.)	
	Max. horsepower (Gross)	31 HP@3000 rpm	
	Total displacement	1261 cc	
	Starting system	Key switch - super glow	
Dimensions	Overall length	2220 mm	
	Overall width	(w/ mower)	1604 mm
		(w/o mower)	1460 mm
	Overall height	(w/ ROPS upright)	1915 mm
(w/ ROPS folded)		1555 mm	
Wheel base		1410 mm	
Tread	Front	975 mm	
	Rear	1150 mm	
Tyre size	Front	15 x 6.0-6 Non-flat	
	Rear	26 x 12.0-12	
Weight (w/ mower) (without fuel)		763 kg	
Transmission system		2-HST w/ Gear reduction	
Speed control		2-hand lever	
Travel speed range	Forward	0-17.0 km/h	
	Reverse	0-8.5 km/h	
Brake type		Wet multi discs, foot applied, released	
PTO	Type	Shaft drive	
	Clutch type	Hydraulic independent PTO clutch with wet multi discs	
	PTO brake	Wet single disc	
Mower deck	Model	RCK60R-331Z	
	Mower lift system	Hydraulic	
	Mower deck type	Pro commercial— Fabricated deck	
	Deck depth	140 mm	
	Belt type	Multi-Belt	
	Deck steel thickness	4.6 mm / 4.2 mm	
	Anti-scalp roller	Swivel	
	Cutting width of mower	60 in.	
	Number of blades	3 blades	
	Cutting height	1 in. ~ 5 in. / 1/4 in. increments	
	Mounting system of mower	Quick joint, parallel linkage	
	Blade tip speed (max.)	17100 FPM	
	Engine stop system		Key stop
Fuel tank capacity		49 ltrs.	
Battery		12 Volts, 51R, 450CCA, 70 min. RC.	
Alternator capacity		14 Amps@14 Volts	
Fuel gauge		Electric	

The company reserves the right to change the above specifications without notice.

This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information.

For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.

For complete operational information, the operator's manual should be consulted.

©2012 Kubota Corporation

Kubota

KUBOTA Tractor Australia Pty Ltd

25-29 Permas Way, TRUGANINA Vic, 3029
 Freecall: 1800 334 653
 Email: sales@kubota.com.au

Web Site: <http://www.kubota.com.au>

CB Norwood Distributors Ltd

PO Box 1265, 888 Tremaine Avenue,
 Palmerston North 0800 KUBOTA
 Tel: 06 356 4920 Fax: 06 356 4939

Web Site: <http://www.kubota.co.nz>